

Lock Out Padlock

HT406



Features

- Non-conductive, lightweight body with high-strength steel shackle.
- Suitable for indoor and outdoor industrial environments.
- Easy to carry and use in lockout/tagout (LOTO) procedures.

Designed for safety lockout/tagout (LOTO) procedures, this padlock helps prevent accidental equipment startup during maintenance or repairs. Constructed with a durable, non-conductive body and a high-strength steel shackle, it resists tampering while ensuring reliable protection. Lightweight, corrosion-resistant, and easy to identify with bright coloring and writable labels, it's ideal for industrial, electrical, and mechanical lockout applications.

Product Specification

Size	Body Height 1-3/4" Body Width 1-1/2"
Weight	7.7 Oz
Material	Nonconductive Plastic & Steel
Packaging Style	Box
Color	Red

Applications

- Industrial Maintenance – Locking out machinery during servicing or repairs.
- Electrical Safety – Securing breaker panels, switches, and disconnects to prevent accidental energization.
- Manufacturing Plants – Used in lockout/tagout (LOTO) programs to isolate hazardous energy sources.

Industries

-  Industrial
-  Maintenance
-  Warehouse

Packaging Information

1 Piece (Shrink Wrap) / Box

24 Boxes / Carton

Carton Size- 7.28 x 7.28 x 4.72 in

Carton Weight- 4.8 lbs

SKU Information

Product SKU	Inner pack UPC	Carton GTIN
BLMS-LOPLK-1	810188144935	00810188144942

